

S6 Option Switch Settings (12V DC)

Supported bill US\$ 1(95, 99), 5(99, 03), 10(99, 04, 06), 20(96, 99, 04)
4bills.

S6 dip-switch settings and functions:

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
Reject US\$ 1	ON											
Accept US\$ 1	OFF											
Reject US\$ 5		ON										
Accept US\$ 5		OFF										
Reject US\$ 10			ON									
Accept US\$ 10			OFF									
Reject US\$ 20				ON								
Accept US\$ 20				OFF								
ES. Quick sleep					ON							
ES. Delay to sleep					OFF							
High Acceptance						ON						
High Security						OFF						
Harness disable							ON					
Harness enable							OFF					
★★ Inhibit Active High								ON				
★ Inhibit Active Low								OFF				
1 pulse / one dollar									OFF	OFF		
2 pulse / one dollar									ON	OFF		
4 pulse / one dollar									OFF	ON		
20 pulse / one dollar									ON	ON		
Interface Timing Conversion	50ms on / 50ms off										OFF	
	100ms on / 100ms off										ON	
Factory define(Always ON)												ON

- ◆ Factory configuration has all switches in the OFF position, except the SW4 of the 4-dips.
- ◆ Harness disable : B.A. will not accept inhibit signal.
Harness enable : B.A. will accept inhibit signal.
- ◆ ES. Quick sleep : Quick sleep on Exception status.
ES. Delay to sleep : Delay to sleep on Exception status.
- ◆ The SW4 of the 4-dips must always be on.

